



RATINGS 400 V - 50 Hz		
Standby	kVA	275
	kWe	220
Prime	kVA	250
	kWe	200

## Benefits & features

### KOHLER premium quality

- Design offices using the latest technical innovations
- Modern fully certified factories
- A cutting edge laboratory
- The generating set, its components and a wide range of options have been fully developed, prototype tested, factory built, and production tested

### KOHLER premium performances

- Optimized and certified sound levels
- Reliable power, even in extreme conditions
- Optimized fuel consumption
- Compact footprint
- Best quality of electricity, high starting and loading capacity, according to ISO8528-5
- Robust base frames and high-quality enclosures
- Protection of installations and people
- Approved in line with the most stringent standards

### Engines

- Premium level engines, in-house or from strong partners
- High power density, small footprint
- Low temperature starting capability
- Long maintenance interval

### Alternator

- Provide industry leading motor starting capability
- Made in Europe
- Built with a class H insulation and IP23

### Cooling

- A compact and complete solution using a mechanically driven radiator fan
- Designed or optimized by KOHLER
- High temperature and altitude product capacity available

### Base frame and enclosure

- High quality steel with enhanced corrosion resistance
- Highly durable QUALICOAT-certified epoxy paint
- Minimum 1000 hours of resistance to salt spray in accordance with ISO12944
- Ergonomic access to allow easy maintenance and connection of the generator
- Robust design optimized for transportation

## GENERAL SPECIFICATIONS

Engine brand	DOOSAN / HYUNDAI
Alternator commercial brand	KOHLER
Voltage (V)	400/230
Standard Control Panel	APM303
Optional control panel	APM403
Optional Control Panel	Terminal block
Optional control panel	M80
Consumption @ 100% load ESP (L/h) *	59
Consumption @ 100% load PRP (L/h) *	53
Emission level	Emission optimization - Stage II Compliant
Type of Cooling	Radiator
Performance class	G3

## GENERATOR SETS RATINGS

	Voltage	Standby Rating			Prime Rating			
		PH	Hz	kWe	kVA	Amps	kWe	kVA
D275	415/240	3	50	220	275	383	200	250
	400/230	3	50	220	275	397	200	250
	380/220	3	50	220	275	418	200	250
	200/115	3	50	220	275	794	200	250
	240 TRI	3	50	220	275	662	200	250
	230 TRI	3	50	220	275	690	200	250

## DIMENSIONS COMPACT VERSION

Length (mm)	2970
Width (mm)	1346
Height (mm)	1708
Tank capacity (L)	390
Dry weight (kg)	2427

## DIMENSIONS SOUNDPROOFED VERSION

Type soundproofing	NOT AVAILABLE
Length (mm)	4100
Width (mm)	1410
Height (mm)	2147
Tank capacity (L)	390
Dry weight (kg)	3171
Acoustic pressure level @1m in dB(A) 50Hz (75% PRP)	79
Acoustic pressure level @7m in dB(A) 50Hz (75% PRP)	69

Reference Conditions: 25°C Air Inlet Temperature, 40°C Fuel Inlet Temperature, 100 kPa Barometric Pressure; 10.7 g/kg of dry air Humidity. Intake Restriction set to maximum allowable limit for clean filter; Exhaust Back pressure set to maximum allowable limit; Fuel density at 0.85 kg/L.

Data was taken from a single engine test according to the test methods, fuel specification and reference conditions stated above and is subjected to instrumentation and engine-to-engine variability. Test conducted with alternate test methods, instrumentation, fuel or reference conditions can yield different results. Data and specifications subject to change without notice.

<b>Engine</b>		
<b>General</b>		
Engine brand	DOOSAN / HYUNDAI	
Engine ref.	P126TI *	
Air inlet system	Turbo	
Fuel	Diesel Fuel	
Emission level	Emission optimization - Stage II Compliant	
Cylinder configuration	L	
Number of cylinders	6	
Displacement (l)	11,05	
Bore (mm) * Stroke (mm)	123 * 155	
Compression ratio	17 : 1	
Speed 50Hz (RPM)	1500	
Maximum stand-by power at rated RPM (kW)	272	
Charge Air coolant	Air/Air	
Frequency regulation, steady state (%)	+/- 0.25%	
Injection Type	Direct	
Governor type	Electronic	
Air cleaner type, models	Dry	
<b>Fuel system</b>		
Maximum fuel pump flow (l/h)	270	
Max head on fuel return line (m fuel)	1	
<b>Consumption with cooling system</b>		
Fuel consumption @ ESP Max Power (l/h)	66,20	
Fuel consumption @ PRP Max Power (l/h)	58,10	
Fuel consumption @ 75% of PRP Power (l/h)	43,60	
Fuel consumption @ 50% of PRP Power (l/h)	30	
<b>Emissions</b>		
Emission PM 50Hz (g/kW.h)	0,06	
Emission CO 50Hz (g/kW.h)	0,6480	
Emission NOx 50Hz (g/kW.h)	5,3320	
Emission HC 50Hz (g/kW.h)	0,3360	
<b>Lubrication System</b>		
Oil system capacity including filters (l)	25	
Min. oil pressure (bar)	0,50	
Max. oil pressure (bar)	10	
Oil sump capacity (l)	23	
Oil consumption 100% ESP 50Hz (l/h)	0,06	
<b>Air Intake system</b>		
Max. intake restriction (mm H2O)	635	
Combustion air flow (l/s)	273	
<b>Exhaust system</b>		
Exhaust gas flow (L/s)	715	PRP
Exhaust gas temperature @ ESP (°C)	560	ESP
Heat rejection to exhaust (kW)	254	
Max. exhaust back pressure (mm H2O)	600	
<b>Cooling system</b>		
Radiator & Engine capacity (l)	50,50	
Fan power 50Hz (kW)	7	
Fan air flow w/o restriction (m3/s)	5	
Available restriction on air flow (mm H2O)	20	
Type of coolant	Glycol-Ethylene	
Radiated heat to ambient (kW)	35	
Heat rejection to coolant HT (kW)	107	
Coolant capacity HT, engine only (l)	19	
Max coolant temperature, Shutdown (°C)	103	
Thermostat begin of opening HT (°C)	71	
Thermostat end of opening HT (°C)	85	

\* Engine reference may be partially modified depending on genset application, options selected by the customer and lead time required.

**Alternator Specifications**

Alternator commercial brand	KOHLER
Kohler Alternator description	KH01381T
Number of pole	4
Number of bearing	Single Bearing
Technology	Brushless
Indication of protection	IP23
Insulation class	H
Number of wires	12
AVR Regulation	Yes
Coupling	Direct
Capacity for maintaining short circuit at 3 In for 10 s	Yes

**Alternator Standard Features**

- All models are brushless, rotating-field alternators
- NEMA MG1, IEEE, and ANSI standards compliance for temperature rise and motor starting
- The AVR voltage regulator provides superior short circuit capability
- Self-ventilated and dip proof construction
- Superior voltage waveform

*Note: See Alternator Data Sheets for alternator application data and ratings, efficiency curves, voltage dip with motor starting curves, and short circuit decrement curves.*

**Application data**

Overspeed (rpm)	2250
Power factor (Cos Phi)	0,80
Voltage regulation at established rating (+/- %)	1
Wave form : NEMA=TIF	<40
Wave form : CEI=FHT	<2
Total Harmonic Distortion in no-load DHT (%)	2,0
Total Harmonic Distortion, on linear load DHT (%)	2,9
Recovery time (Delta U = 20% transient) (ms)	200

**Performance datas**

Continuous Nominal Rating 40°C (kVA)	250
Unbalanced load acceptance ratio (%)	8
Peak motor starting (kVA) based on x% voltage dip power factor at 0.3	

**Dimensions compact version**

Length (mm) * Width (mm) * Height (mm)	2970 * 1346 * 1708
Dry weight (kg)	2427
Tank capacity (L)	390

**M237 soundproofed version - Not compliant with 2000/14/CE noise emissions Directive\*\***

Length (mm) * Width (mm) * Height (mm)	4100 * 1410 * 2147
Dry weight (kg)	3171
Tank capacity (L)	390
Acoustic pressure level @1m in dB(A) 50Hz (75% PRP)	79
Sound power level guaranteed (Lwa) 50Hz (75% PRP)	99
Acoustic pressure level @7m in dB(A) 50Hz (75% PRP)	69

**Dimensions DW compact version**

Length (mm) * Width (mm) * Height (mm)	4152 * 1410 * 1922
Dry weight (kg)	2792
Tank capacity (L)	950

**M237 DW soundproofed version - Not compliant with 2000/14/CE noise emissions Directive\*\***

Length (mm) * Width (mm) * Height (mm)	4152 * 1410 * 2361
Dry weight (kg)	3682
Tank capacity (L)	950
Acoustic pressure level @1m in dB(A) 50Hz (75% PRP)	79
Sound power level guaranteed (Lwa) 50Hz (75% PRP)	99
Acoustic pressure level @7m in dB(A) 50Hz (75% PRP)	69

\* dimensions and weight without options

\*\*Indoor use only in the European economic area, the United Kingdom, Iceland, Norway, and Liechtenstein.

**Basic terminal block****M80****APM303**

It is used as a basic terminal block for connecting a control unit. Offers the following functions:

- emergency stop button
- customer connection terminal block
- CE certified

The M80 is a dual-function control panel. It can be used as a basic terminal block for connecting a control unit and as an instrument panel with a direct read facility, with displays giving a global view of your generating set's basic parameters. Offers the following functions:

- Engine parameters: tachometer, working hours counter, coolant temperature indicator, oil pressure indicator
- emergency stop button
- customer connection terminal block
- CE certified

The APM303 is a versatile unit which can be operated in manual or automatic mode. It offers the following features:


- Measurements: phase-to-neutral and phase-to-phase voltages, fuel level (In option : active power currents, effective power, power factors, Kw/h energy meter, oil pressure and coolant temperature levels)
- Supervision: Modbus RTU communication on RS485
- Reports: (In option : 2 configurable reports)
- Safety features: Overspeed, oil pressure, coolant temperatures, minimum and maximum voltage, minimum and maximum frequency (Maximum active power P<66kVA)
- Traceability: Stack of 12 stored events

For further information, please refer to the data sheet for the APM303

**BASIC GENERATING SET AND POWER PLANT CONTROL**

The APM403 is a versatile control unit which allows operation in manual or automatic mode

- Measurements : voltage and current
- kW/kWh/kVA power meters
- Standard specifications: Voltmeter, Frequency meter.
- Optional : Battery ammeter.
- J1939 CAN ECU engine control
- Alarms and faults: Oil pressure, Coolant temperature, Overspeed, Start-up failure, alternator min/max, Emergency stop button.
- Engine parameters: Fuel level, hour counter, battery voltage.
- Optional (standard at 24V): Oil pressure, water temperature.
- Event log/ Management of the last 300 gensex events.
- Mains and gensex protection
- Clock management
- USB connections, USB Host and PC,
- Communications : RS485 INTERFACE
- ModBUS protocol /SNMP
- Optional : Ethernet, GPRS, remote control, 3G, 4G, Websupervisor, SMS, E-mails

**APM403**

## STANDARD SCOPE OF SUPPLY

All our gensets are fitted with:

- Industrial water cooled DIESEL engine
- Electric starter & charge alternator
- Standard air filter
- Schneider or ABB electric circuit breaker, adapted to the short-circuit current of the generating set
- Single bearing alternator IP 23 T° rise/ insulation to class H/H
- Welded steel base frame with 85% vibration attenuation mounts
- 4 lifting points on the chassis, lifting bar on the top included from 165 kVA ESP or optional
- highly durable QUALICOAT certified epoxy paint
- frame height optimized to allow it to be moved safely by forklift
- enclosure made of new high-quality European steel with enhanced corrosion resistance
- IP 64 locks, made from stainless materials
- enclosures and base frames tested and analyzed by the French Corrosion Institut
- 100% of tanks tested for permeability
- Personal protection ensured by protective grilles on hot and rotating parts
- Separate 9 dB(A) silencer
- Fuel tank welded inside the genset frame
- Retention bund included for gensets up to 110 kVA ESP
- Charged DC starting battery with electrolyte
- Emergency stop button on the outside
- Flexible fuel lines & lub oil drain cock
- Exhaust outlet with flexible and flanges
- User's manual (1 copy)
- Packing under plastic film

### Excluded from the supply:

- For XPRESS products, from 25 to 1500 kVA: oil and antifreeze liquid

## CODES AND STANDARDS

Engine-generators set is designed and manufactured in facilities certified to standards ISO9001:2015 & ISO14001:2015. The generator sets and its components are prototype-tested, factory built and production tested and are in compliance with the relevant standards:

- Machinery Directive 2006/42/EC of May 17th 2006
- EMC Directive 2014/30/UE
- Safety objectives set out in the Low Voltage Directive 2014/35/UE
- EN ISO 8528-13, EN 60034-1, EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 55011, EN 1679-1 et EN 60204-1

## POWER RATINGS DEFINITION according to ISO8528-1 (2018-02 edition) and ISO-3046-1

**Emergency Standby Power (ESP):** The standby rating is applicable to varying loads for the duration of a power outage. There is no overload capability for this rating. Average load factor per 24 hours of operation is <70%.

**Prime Power (PRP):** At varying load, the number of generator set operating hours is unlimited. A 10% overload capacity is available for one hour within 12 hour of operation. Average load factor per 24 hours of operation is <70%.



Industrial Diesel Generator Set - D275

50 Hz

## TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Intlet Temperature, of a barometric pressure of 100 kPa (100 m A.S.L), and 30% relative humidity. For particular conditions in your installation, refer to the derating table.

## WARRANTY INFORMATIONS

Standard Warranty Period:

- for Products in "back-up" service
  - o 30 months from the date the Product leaves the plant
  - o 24 months from the Product's commissioning date
  - o 1,000 running hours

The warranty expires when one of the above conditions is met.

- for Products in "prime" or "continuous" service (continuous supply of electricity, either in the absence of any normal electricity grid or to complement the grid),
  - o 18 months from the date the Product leaves the plant
  - o 12 months from the Product's commissioning date
  - o 2,500 running hours

The warranty expires when one of the above conditions is met.

For more details regarding conditions of application and scope of the warranty please refer to our General "terms & conditions of sales".

---

Reference Conditions: 25°C Air Inlet Temperature, 40°C Fuel Inlet Temperature, 100 kPa Barometric Pressure; 10.7 g/kg of dry air Humidity. Intake Restriction set to maximum allowable limit for clean filter; Exhaust Back pressure set to maximum allowable limit; Fuel density at 0.85 kg/L.

Data was taken from a single engine test according to the test methods, fuel specification and reference conditions stated above and is subjected to instrumentation and engine-to-engine variability. Test conducted with alternate test methods, instrumentation, fuel or reference conditions can yield different results. Data and specifications subject to change without notice.