



RATINGS 400 V - 50 Hz			
Standby	kVA	650,00	
	kWe	520,00	
Prime	kVA	591,00	
	kWe	473,00	



Benefits & features

KOHLER premium quality

- Design offices using the latest technical innovations
- Modern fully certified factories
- A cutting edge laboratory
- The generating set, its components and a wide range of options have been fully developed, prototype tested, factory built, and production tested
- Approved for use with HVO (Hydrotreated Vegetable Oil) according to EN15940

KOHLER premium performances

- Optimized and certified sound levels
- Reliable power, even in extreme conditions
- Optimized fuel consumption
- Compact footprint
- Best quality of electricity, high starting and loading capacity, according to ISO8528-5
- Robust base frames and high-quality enclosures
- Protection of installations and people
- Approved in line with the most stringent standards

Engines

- Premium level engines, in-house or from strong partners
- High power density, small footprint
- Low temperature starting capability
- Long maintenance interval

Alternator

- Provide industry leading motor starting capability
- Made in Europe
- Built with a class H insulation and IP23

Cooling

- A compact and complete solution using a mechanically driven radiator fan
- Designed or optimized by KOHLER
- High temperature and altitude product capacity available

Base frame and enclosure

- High quality steel with enhanced corrosion resistance
- Highly durable QUALICOAT-certified epoxy paint
- Minimum 1000 hours of resistance to salt spray in accordance with ISO12944
- Ergonomic access to allow easy maintenance and connection of the generator
- Robust design optimized for transportation

GENERAL SPECIFICATIONS

Engine brand	VOLVO
Alternator commercial brand	KOHLER
Voltage (V)	400/230
Standard Control Panel	APM403
Optional control panel	M80-D
Optional Control Panel	Terminal block
Consumption @ 100% load ESP (L/h) *	129
Consumption @ 100% load PRP (L/h) *	115
Emission level	Emission optimization - Stage II Compliant
Type of Cooling	Radiator
Performance class	G3

GENERATOR SETS RATINGS

	Voltage	PH	Hz	Standby Rating			Prime Rating	
				kWe	kVA	Amps	kWe	kVA
V650C2	415/240	3	50	520,00	650,00	904	473,00	591,00
	400/230	3	50	520,00	650,00	938	473,00	591,00
	380/220	3	50	520,00	650,00	988	473,00	591,00
	200/115	3	50	520,00	650,00	1876	473,00	591,00
	240 TRI	3	50	520,00	650,00	1564	473,00	591,00
	230 TRI	3	50	520,00	650,00	1632	473,00	591,00
	220/127	3	50	527,00	659,00	1729	479,00	599,00

DIMENSIONS COMPACT VERSION

Length (mm)	3620
Width (mm)	1892
Height (mm)	1993
Tank capacity (L)	717,00
Dry weight (kg)	4180,00

DIMENSIONS SOUNDPROOFED VERSION

Type soundproofing	M240
Length (mm)	5320
Width (mm)	2071
Height (mm)	2658
Tank capacity (L)	717,00
Dry weight (kg)	5930,00
Acoustic pressure level @1m in dB(A) 50Hz (75% PRP)	84
Acoustic pressure level @7m in dB(A) 50Hz (75% PRP)	74

* Volumetric Fuel consumption is up to 4% higher when using HVO than Diesel Fuel

Reference Conditions: 25°C Air Inlet Temperature, 40°C Fuel Inlet Temperature, 100 kPa Barometric Pressure; 10.7 g/kg of dry air Humidity. Intake Restriction set to maximum allowable limit for clean filter; Exhaust Back pressure set to maximum allowable limit; Fuel density at 0.85 kg/L.

Data was taken from a single engine test according to the test methods, fuel specification and reference conditions stated above and is subjected to instrumentation and engine-to-engine variability. Test conducted with alternate test methods, instrumentation, fuel or reference conditions can yield different results. Data and specifications subject to change without notice.

Engine			
General		Lubrication System	
Engine brand	VOLVO	Oil system capacity including filters (l)	48,00
Engine ref.	TAD1642GE-B *	Min. oil pressure (bar)	2,8
Air inlet system	Turbo	Max. oil pressure (bar)	6,5
Fuel	Diesel Fuel/HVO	Oil sump capacity (l)	42,00
Emission level	Emission optimization - Stage II Compliant	Oil consumption 100% ESP 50Hz (l/h)	0,110
Cylinder configuration	L	Air Intake system	
Number of cylinders	6	Max. intake restriction (mm H2O)	510
Displacement (l)	16,12	Combustion air flow (l/s)	650,00
Bore (mm) * Stroke (mm)	144,00 * 165,0	Exhaust system	
Compression ratio	16.8 : 1	Exhaust gas flow (L/s)	PRP 1573,0ESP 1708,0
Speed 50Hz (RPM)	1500	Exhaust gas temperature @ ESP (°C)	482
Maximum stand-by power at rated RPM (kW)	565,0	Heat rejection to exhaust (kW)	427
Charge Air coolant	Air/Air	Max. exhaust back pressure (mm H2O)	1020
Frequency regulation, steady state (%)	+/- 0.25%	Cooling system	
Injection Type	Direct	Radiator & Engine capacity (l)	60,00
Governor type	Electronic	Fan power 50Hz (kW)	9,00
Air cleaner type, models	Dry	Fan air flow w/o restriction (m3/s)	10,00
Fuel system		Available restriction on air flow (mm H2O)	30,00
Maximum fuel pump flow (l/h)	180,0	Type of coolant	Glycol-Ethylene
Max head on fuel return line (m fuel)	2,0	Radiated heat to ambient (kW)	20,0
Maximum allowed inlet fuel temperature (°C)	60	Heat rejection to coolant HT (kW)	218
Consumption with cooling system		HT circuit flow rate (l/min)	384
Fuel consumption @ ESP Max Power (l/h)	130,3	Coolant capacity HT, engine only (l)	33,0
Fuel consumption @ PRP Max Power (l/h)	116,7	Outlet coolant temperature (°C)	93
Fuel consumption @ 75% of PRP Power (l/h)	88,9	Max coolant temperature, Shutdown (°C)	107,0
Fuel consumption @ 50% of PRP Power (l/h)	59,9	Max. pressure at inlet of HT water pump (mbar)	1000
Emissions		Thermostat begin of opening HT (°C)	82
Emission PM 50Hz (g/kW.h)	0,1100	Thermostat end of opening HT (°C)	96
Emission CO 50Hz (g/kW.h)	0,670		
Emission NOx 50Hz (g/kW.h)	5,420		
Emission HC 50Hz (g/kW.h)	0,250		

* Engine reference may be partially modified depending on genset application, options selected by the customer and lead time required.

Alternator Specifications

Alternator commercial brand	KOHLER
Kohler Alternator description	KH02713T
Number of pole	4
Number of bearing	Single Bearing
Technology	Brushless
Indication of protection	IP23
Insulation class	H
Number of wires	12
AVR Regulation	Yes
Coupling	Direct
Capacity for maintaining short circuit at 3 In for 10 s	Yes

Application data

Overspeed (rpm)	2250
Power factor (Cos Phi)	0,8
Voltage regulation at established rating (+/- %)	0,50
Wave form : NEMA=TIF	<40
Wave form : CEI=FHT	<2
Total Harmonic Distortion in no-load DHT (%)	2,4
Total Harmonic Distortion, on linear load DHT (%)	2,2
Recovery time (Delta U = 20% transient) (ms)	200

Performance datas

Continuous Nominal Rating 40°C (kVA)	625,0
Unbalanced load acceptance ratio (%)	8
Peak motor starting (kVA) based on x% voltage dip power factor at 0.3	

Alternator Standard Features

- All models are brushless, rotating-field alternators
- NEMA MG1, IEEE, and ANSI standards compliance for temperature rise and motor starting
- The AVR voltage regulator provides superior short circuit capability
- Self-ventilated and dip proof construction
- Superior voltage waveform

Note: See Alternator Data Sheets for alternator application data and ratings, efficiency curves, voltage dip with motor starting curves, and short circuit decrement curves.

Dimensions compact version

Length (mm) * Width (mm) * Height (mm)	3620 * 1892 * 1993
Dry weight (kg)	4180,00
Tank capacity (L)	717,00

**M240 - Dimensions soundproofed version**

Length (mm) * Width (mm) * Height (mm)	5320 * 2071 * 2658
Dry weight (kg)	5930,00
Tank capacity (L)	717,00
Acoustic pressure level @1m in dB(A) 50Hz (75% PRP)	84
Sound power level guaranteed (Lwa) 50Hz (75% PRP)	105
Acoustic pressure level @7m in dB(A) 50Hz (75% PRP)	74

**Dimensions DW compact version**

Length (mm) * Width (mm) * Height (mm)	5367 * 2153 * 2268
Dry weight (kg)	5100,00
Tank capacity (L)	2420,00

**M240 - Dimensions DW soundproofed version**

Length (mm) * Width (mm) * Height (mm)	5367 * 2153 * 2933
Dry weight (kg)	6810,00
Tank capacity (L)	2420,00
Acoustic pressure level @1m in dB(A) 50Hz (75% PRP)	84
Sound power level guaranteed (Lwa) 50Hz (75% PRP)	105
Acoustic pressure level @7m in dB(A) 50Hz (75% PRP)	74

* dimensions and weight without options

Reference Conditions: 25°C Air Inlet Temperature, 40°C Fuel Inlet Temperature, 100 kPa Barometric Pressure; 10.7 g/kg of dry air Humidity. Intake Restriction set to maximum allowable limit for clean filter; Exhaust Back pressure set to maximum allowable limit; Fuel density at 0.85 kg/L.

Data was taken from a single engine test according to the test methods, fuel specification and reference conditions stated above and is subjected to instrumentation and engine-to-engine variability. Test conducted with alternate test methods, instrumentation, fuel or reference conditions can yield different results. Data and specifications subject to change without notice.

Basic terminal block



It is used as a basic terminal block for connecting a control unit. Offers the following functions:

- emergency stop button
- customer connection terminal block
- CE certified

M80-D




The M80-D can be used as a basic terminal block for connecting a control unit and as an instrument panel with a highly intuitive LCD screen giving an overview of your generating set's basic parameters:

- Oil gauge
- Coolant temperature
- Oil temperature
- Engine speed
- Battery voltage
- Charge air temperature
- Fuel consumption
- etc.

The engine main functions can be controlled and events are recorded to facilitate diagnostics:

- Starting
- Speed adjustment
- Stopping
- Droop
- etc.

APM403



BASIC GENERATING SET AND POWER PLANT CONTROL

The APM403 is a versatile control unit which allows operation in manual or automatic mode

- Measurements : voltage and current
- kW/kWh/kVA power meters
- Standard specifications: Voltmeter, Frequency meter.
- Optional : Battery ammeter.
- J1939 CAN ECU engine control
- Alarms and faults: Oil pressure, Coolant temperature, Overspeed, Start-up failure, alternator min/max, Emergency stop button.
- Engine parameters: Fuel level, hour counter, battery voltage.
- Optional (standard at 24V): Oil pressure, water temperature.
- Event log/ Management of the last 300 genset events.
- Mains and genset protection
- Clock management
- USB connections, USB Host and PC,
- Communications : RS485 INTERFACE
- ModBUS protocol /SNMP
- Optional : Ethernet, GPRS, remote control, 3G, 4G,
- Websupervisor, SMS, E-mails

STANDARD SCOPE OF SUPPLY

All our gensets are fitted with:

- Industrial water cooled DIESEL engine
- Electric starter & charge alternator
- Standard air filter
- Schneider or ABB electric circuit breaker, adapted to the short-circuit current of the generating set
- Single bearing alternator IP 23 T° rise/ insulation to class H/H
- Welded steel base frame with 85% vibration attenuation mounts
- 4 lifting points on the chassis, lifting bar on the top included from 165 kVA ESP or optional
- highly durable QUALICOAT certified epoxy paint
- frame height optimized to allow it to be moved safely by forklift
- enclosure made of new high-quality European steel with enhanced corrosion resistance
- IP 64 locks, made from stainless materials
- enclosures and base frames tested and analyzed by the French Corrosion Institut
- 100% of tanks tested for permeability
- Personal protection ensured by protective grilles on hot and rotating parts
- Separate 9 dB(A) silencer
- Fuel tank welded inside the genset frame
- Retention bund included for gensets up to 110 kVA ESP
- Charged DC starting battery with electrolyte
- Emergency stop button on the outside
- Flexible fuel lines & lub oil drain cock
- Exhaust outlet with flexible and flanges
- User's manual (1 copy)
- Packing under plastic film
- Delivered with oil and antifreeze liquid

CODES AND STANDARDS

Engine-generators set is designed and manufactured in facilities certified to standards ISO9001:2015 & ISO14001:2015. The generator sets and its components are prototype-tested, factory built and production tested and are in compliance with the relevant standards:

- Machinery Directive 2006/42/EC of May 17th 2006
- EMC Directive 2014/30/UE
- Safety objectives set out in the Low Voltage Directive 2014/35/UE
- EN ISO 8528-13, EN 60034-1, EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 55011, EN 1679-1 et EN 60204-1

POWER RATINGS DEFINITION according to ISO8528-1 (2018-02 edition) and ISO-3046-1

Emergency Standby Power (ESP): The standby rating is applicable to varying loads for the duration of a power outage. There is no overload capability for this rating. Average load factor per 24 hours of operation is <70%.

Prime Power (PRP): At varying load, the number of generator set operating hours is unlimited. A 10% overload capacity is available for one hour within 12 hour of operation. Average load factor per 24 hours of operation is <70%.

TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPa (100 m A.S.L), and 30% relative humidity. For particular conditions in your installation, refer to the derating table.

WARRANTY INFORMATIONS

Standard Warranty Period:

- for Products in "back-up" service
 - o 30 months from the date the Product leaves the plant
 - o 24 months from the Product's commissioning date
 - o 1,000 running hours

The warranty expires when one of the above conditions is met.

- for Products in "prime" or "continuous" service (continuous supply of electricity, either in the absence of any normal electricity grid or to complement the grid),
 - o 18 months from the date the Product leaves the plant
 - o 12 months from the Product's commissioning date
 - o 2,500 running hours

The warranty expires when one of the above conditions is met.

For more details regarding conditions of application and scope of the warranty please refer to our General "terms & conditions of sales".